




RM-8/RM-47 top level




RF top level




RF shields and vias




HELGO




RX front end and antenna switch




RFMD 9250 power amplifier and power detection



DCT45 common baseband top level




UEMEK power management




NOTE: On system sheet connect battery terminal to Zocus 'BATTERY_TERMINAL' pin (make no other connection directly to the battery terminal)
 Connect VBAT global to 'VBAT' pin on Zocus block
 ALL phone current must flow through Zocus block (i.e. all BB, RF, PA)
 VBATBB is the main baseband battery voltage global
 NOTE: This sheet only to be used with Li battery products as 6V3 capacitors do not meet derating requirements when Ni batteries are used
 NOTE: 2x8 IR modules are not supported


UEME ADC filter block




Light filtering




PWR resistor




DC_DC for TIKU and VIO



TEA 5761




Differential stereo



GENIO and GPIO connection block

TIKU GPIO & GENIO BUSES




- ◊ G_APE(15:0)
- ◊ G_CDMA(11:0)
- ◊ G_GPS(7:0)
- ◊ G_SIM(7:0)
- ◊ G_MMC(7:0)
- ◊ G_LPRF(23:0)
- ◊ G_AUDIO(11:0)


BOM detect

	GENIO(7)	GENIO(1)
PA	R3700 Pull up to '1'	R3702 Pull up to '1'
RFMD	Not assy	Not assy
Renesas	Not assy	Assy
Agilent	Assy	Not assy
4th manf	Assy	Assy




WP pull-up for both flashes




IR module



MultiGND symbol bypass




GSM RF - baseband interface




IPA1 AND IPA2 ARE USED IN RF, THE TOLERANCE OF R2902 IS 1% (0402, 1430873)


64Mbit 1v8 SDRAM memory




Testpoints based Ostrich interface




HWA




Br45 system connector





Br45 audio




Current measure



128Mbit NOR




Keyboard UI




TIKU implementation

DCT4.0



Discrete decoupling capacitors for TIKU




Copyright (C) Nokia Corporation. All rights reserved.
 THIS DRAWING IS PROTECTED BY COPYRIGHT AS AN UNPUBLISHED WORK.
 UNAUTHORIZED REPRODUCTION OF THIS DRAWING IS NOT PERMITTED.



Name	Discrete decoupling capacitors for Tiku	Appr	dd-mmm-yy
Assoc	DCT4 Common Baseband	Des.	M. Coombes 25-Feb-02
		Dr.	AKOURI 29-Jun-04


TIKU EDGE bus conversion sheet




5 pine production test pattern

OUT


Module ID




SIM reader




Upper block




RM-8 assembly values diagram, bottom



RM-8 assembly values diagram, top



RM-47 assembly values diagram, bottom



RM-47 assembly values diagram, top

