



KSH13009H


HIGH VOLTAGE SWITCH MODE APPLICATIONS

High Speed Switching

Suitable for Switching Regulator and Motor Control

ABSOLUTE MAXIMUM RATINGS ($T_a=25$)

T_{stg} —Storage Temperature.....	-55~150
T_j —Junction Temperature.....	150
P_C —Collector Dissipation($T_c=25$).....	130W
V_{CBO} —Collector-Base Voltage.....	700V
V_{CEO} —Collector-Emitter Voltage.....	400V
V_{EBO} —Emitter-Base Voltage.....	9V
I_C —Collector Current (DC)	12A
I_B —Base Current.....	6A



ELECTRICAL CHARACTERISTICS ($T_a=25$)

Symbol	Characteristics	Min	Typ	Max	Unit	Test Conditions
BVCEO	Collector-Emitter Breakdown Voltage	400			V	$I_C=10mA, I_B=0$
IEBO	Emitter-Base Cut-off Current			1	mA	$V_{EB}=9V, I_C=0$
HFE (1)	DC Current Gain	8		40		$V_{CE}=5V, I_C=5A$
HFE (2)		6		30		$V_{CE}=5V, I_C=8A$
VCE(sat1)	Collector- Emitter Saturation Voltage			1	V	$I_C=5A, I_B=1A$
VCE(sat2)				1.5	V	$I_C=8A, I_B=1.6A$
VCE(sat3)				3	V	$I_C=12A, I_B=3A$
VBE(sat1)	Base-Emitter Saturation Voltage			1.2	V	$I_C=5A, I_B=1A$
VBE(sat2)				1.6	V	$I_C=8A, I_B=1.6A$
Cob	Output Capacitance		180		pF	$V_{CB}=10V, f=0.1MHz$
ft	Current Gain-Bandwidth Product	4			MHz	$V_{CE}=10V, I_C=0.5A$
ton	Turn On Time			1.1	μs	$V_{CC}=125V, I_C=8A,$ $I_{B1}=1.6A, I_{B2}=-1.6A$ $R_L=15.6$
tSTG	Storage Time			3.0	μs	
tF	Fall Time			0.7	μs	




Figure 1. DC current Gain




Figure 2. Base-Emitter Saturation Voltage
Collector-Emitter Saturation Voltage




Figure 3. Collector Output Capacitance




Figure 4. Turn On Time




Figure 5. Turn Off Time




Figure 6. Forward Bias Safe Operating Area




Figure 7. Reverse Bias Safe Operating Area




Figure 8. Power Derating